

ASR1100A/1000A/ASR1100A-D/1000A-D

RFID Reader



ASR1100A/1000A
ASR1100A-D/1000A-D

Features

- > Wiegand(1000A) or RS-485 protocol(1100A)
- > Default IC (Mifare) card ("-D" means ID EM card)
- > Blue backlight
- > Watch dog function ensure device free from halting
- > Beep and indicator
- > Surface mounted installation

ASR1100A/1000A/ASR1100A-D/1000A-D

Technical Specifications

Model	ASR1100A/ ASR1100A-D	ASR1000A/ ASR1000A-D
System		
Main Processor	8 Bit	
Read		
Read Format	13.56MHz(Mifare)/125KHz("-D" EM, Optional)	
Read Range	6-8cm (max.)	
Response time	<0.1s	
Function		
Tamper Alarm	Yes	
Interface		
To Controller	RS485	Wiegand
General		
LCD Display	Blue backlight	
Beep Tone	Buzzer	
Ingress protection	IP55	
Power Supply	9-15VDC/100mA	
Working Environment	-30°C - +60°C	
Working Humidity	≤95%	
Dimension(W×D×H)	135mm*86mm*12mm	
Weight	0.25Kg	

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.