

LDH22-SAI200 22'' Wall-mounted Digital Signage



Features :

 \cdot Industrial design, support video, picture, text, audio and other multimedia information released, made for advertising industry

• Support remote timing switch function, can be customized holidays, spring, winter and other different dates, different time of the timer switch function

 \cdot Support cycle play, specified time play, inter-cut, interval play and so on

 \cdot Support multi-level permission settings and management, unaudited programs can not be added to the schedule and play at the terminal

 \cdot Support remote screen capture function, look over the current play state of the terminal

 \cdot Support the program material off the network or outage resume function, greatly save bandwidth and network flux



	Interface	
	RJ45	1
	USB 2.0	2
	SD	1
	RS232	1
	Wi-Fi	1
	Others	
	Dimension	533.0×354×45.5mm
	Package Size	660×188×431mm
	Net Weight	7kg
	Body Material	Metal plate
	Protection	IP50
	Installation Mode	Wall-mounted
	Display Mode	Horizontal, Vertical
	Power	AC100-240V, 50/60Hz
	Standard Consumption	18W
	Standby Consumption	≤0.5W

Technical Specification

Specification

Built in Loudspeaker

Model		LDH22-SAI200
Panel S	iize	22" TFT LCD
Display	Ratio	16:9
Maxim	um Resolution	1920×1080
Display	Color	16.7M
Brightr	ness (nits)	250cd/m ²
Contra	st	3000:1
Viewin	g Angle	178°/178°
Respor	ise Time	18ms
Backlig	ht	LED
Perfo	ormance	
System	1	Android4.4
RAM		1GB
Interna	al Storage	8GB
Decod	ng Ability	1CH@4K or 4CH@1080P
Netwo	rk Mode	Wired, Wi-Fi, 3G/4G(optional)

8Ω/2W×2

LDH22-SAI200

Work Environment

Temperature: -10[°]C~+55[°]C Humidity: 10%~90%



Dimensions(mm)



