


SPECIFICATION

CONSTRUCTION & DIMENSION

Conductor	Material:	CCA
	Size:	24AWG*4P
	Construction:	1/0.5±0.01MM
Insulation	Material:	PE
	Avg. Thickness:	0.20MM
	Min. Thickness:	0.19MM
	Diameter:	0.88±0.01MM
Inner Layer	Direction:	S
	Pitch:	30mm underneath
Outside Layer	Direction:	S
	Pitch:	200mm underneath
Separate	Material:	/
	Construction:	/
Shielding	Material:	/
	Coverage:	/
	Drain Wire:	/
	Material:	/
Filler	Material:	Nylon
	Coverage:	/
Jacket	Material:	PVC
	Avg. Thickness:	0.55MM
	Min. Thickness:	0.50MM
	Diameter:	(4.5*3.4) ±0.3mm
Marking	Color:	Optional
	Optional	
Packing	Optional	



Insulation Color:
 1. Orange&White/Orange
 2. Green&White/Green

CROSS-SECTION

ELECTRICAL PROPERTIES

Solid conductor resistance	:	≤18.5 Ω/100M at 20°C
Insulation Resistance	:	Min. 5000mega ohms-km at 20°C
Dielectric Test	:	1000V DC/1min;No Breakdown

DESCRIPTION

Rating Temperature	:	65°C
Voltage Rating	:	30V

Description: LAN CABLE CAT3 UTP 1/0.5CCA*2P PVC

Customer : Drawing NO. : N171026002

Drawing Yang 2017.10.26 UNIT:MM REV.:A PART NO. :

Checked

Approved